

Clear View



Clear View, glass with style! For a technical glance at the future of glass curtains.

info@gtsglass.com



Introducing the new Clear View system.

This robust glass curtain system features thick walled profiles giving strength and durability, containing wheels of 40mm diameter with three bearings per unit and their unique anti jam design, these are connected with an 8mm stainless steel bolt to the re-enforced base also of stainless steel.

The glass panels are bolted to the profiles via the end caps through a hole in the glass, they are not glued thus giving rapid assemble, the end caps have a male and female design this stopping weather penetration also, featuring vertical profiles at each end to seal around the glass with their cups to receive the glazing profiles.

Featuring the compensation profile enabling easy adjustment of the panels, with a total compensation of over 18mm.

Two bottom profiles available, one for surface mounting and the other for embedding in the floor to leave a nearly flush surface.

The larger wheels allowing a smooth ride around corners of up to and beyond 90 degrees allowing you to stack panels to the desired area.

There is no need for an opening arm sticking out into the room and has its own top cover plate to cover the exit gates, allowing the fixing of blinds or curtains closer to the unit.

The system is certified with the following CE certificates.

Resistance to wind loads UNE-EN 1932:2014
Performance requirements including safety UNE-EN 13561:2015/AC:201
Both with pressure positive and negative CLASS 6,

Air Permeability / UNE-EN 1026: 2017 UNE-EN 12207:2017 CLASS 1 Water tightness / UNE-EN 1027: 2017 UNE-EN 12208:2000 CLASS 4A.